

Kelin Epoxy 係一種高強度、高耐久之環氧樹脂，廣泛應用於建築、工業及交通等領域。其特點包括：
 1. 高強度：具有極高的抗壓及抗拉強度，能承載重負荷。
 2. 高耐久：具有優異的耐化學腐蝕及耐磨性能，能長期保持穩定。
 3. 易於施工：可與多種基材（如混凝土、金屬、木材等）良好粘附，施工簡便。
 4. 環保無毒：不含揮發性有機物（VOC），對環境及人體健康無害。
 5. 美觀大方：可調製成多種顏色及光澤度，提升裝飾效果。
 6. 快速固化：可在短時間內完成固化，節省施工時間。
 7. 抗裂性能：能有效防止基材開裂，延長使用壽命。
 8. 防火阻燃：具有優良的防火性能，能防止火災蔓延。
 9. 抗潮濕：能防止潮濕環境對基材的損壞。
 10. 抗污易潔：表面光滑，易於清潔及維護。

Subbase Epoxy Resin 係一種專為地盤工程設計之環氧樹脂，具有以下特點：
 1. 高強度：能承載重負荷，確保地盤穩定。
 2. 高耐久：具有優異的耐壓及抗裂性能，能長期使用。
 3. 易於施工：可與多種基材良好粘附，施工簡便。
 4. 環保無毒：不含揮發性有機物（VOC），對環境及人體健康無害。
 5. 快速固化：可在短時間內完成固化，節省施工時間。
 6. 抗裂性能：能有效防止地盤開裂，延長使用壽命。
 7. 抗潮濕：能防止潮濕環境對地盤的損壞。
 8. 抗污易潔：表面光滑，易於清潔及維護。



係一種高強度、高耐久之環氧樹脂，廣泛應用於建築、工業及交通等領域。



01

Clean the tiles and keep it dry



02

Polish with tile wax except the glazed tile



03

Open & Watch, both sides can extruded meanwhile



04

Screw on the nozzle, put on the grout gun



05

Inclined cut the top of the nozzle in 45°



06

Squeeze out 60-80cm long grout in the forepart



07

Evenly squeeze out the tile agent along the gap




08

Press the grout with professional glue-press tools



09

Don't touch in 4-5 hours and remove excess grout then.



10

Keep the tiles dry in 24 hours

□□□□□□□□□□□□□□□□□□□□□□□□□□□□



Two Component Caulking Gun



02




03



04



05



06



07



08



09

Cutter Knife

Pointing trowel

Brush

Forming Stick

Perching Knife

Masking Tape

Stainless Steel Ball

Cleaning Awl

□□□□□□



□□□□□□□□□□



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

□□□□□□□□

