



01 Clean the tiles and keep it dry

02 Polish with tile wax except the glazed tile

03 Open & Watch, both sides can extruded meanwhile

04 Screw on the nozzle, put on the grout gun

05 Inclined cut the top of the nozzle in 45°

06 Squeeze out 60-80cm long grout in the forefront

07 Evenly squeeze out the tile agent along the gap

08 Press the grout with professional glue-press tools

09 Don't touch in 4-5 hours and remove excess grout then.

10 Keep the tiles dry in 24 hours

□□□□□□□□□□□□□□□□□□□□□□□□□□□□



| | | | | | | | |
|--------------------|-----------------------|-------------|---------------------|----------------------|--------------------|----------------------------|--------------------|
| 02 Cutter Knife | 03 Pointing trowel | 04 Brush | 05 Forming Stick | 06 Perching Knife | 07 Masking Tape | 08 Stainless Steel Ball | 09 Cleaning Awl |
|--------------------|-----------------------|-------------|---------------------|----------------------|--------------------|----------------------------|--------------------|

□□□□□□□□□□□□□□□□□□□□



XXXXXXXXXXXXXXXXXXXXXXXXXXXX



XXXXXXXXXXXX



XXXXXXXXXXXXXXXXXXXX



XXXXXXXXXXXX



XXXXXX



XXXXXXXXXXXX



XXXXXXXXXXXXXXXXXXXXXXXXXXXX



XXXXXXXXXXXX



XXXXXX

XXXXXXXXXX

