

Kelin Epoxy 係一種高強度、高耐久之環氧樹脂，廣泛應用於建築、工業及交通等領域。其特點包括：  
 1. 高強度：具有極高的抗拉、抗壓及抗剪強度。  
 2. 高耐久：能抵抗化學腐蝕、磨損及老化。  
 3. 易於施工：可與多種基材（如混凝土、金屬、木材）良好粘結。  
 4. 環保無毒：不含揮發性有機物（VOC），施工後無異味。  
 5. 顏色多樣：可根據需求調配成各種顏色，增加美觀性。  
 6. 快速固化：可在短時間內達到使用強度。  
 7. 抗裂性能：能減少基材因溫度變化或濕度波動產生的裂縫。  
 8. 防水防潮：具有優異的防水性能，適用於地下室、浴室等潮濕環境。  
 9. 耐磨損：表面硬度高，能抵抗日常使用中的刮擦與磨損。  
 10. 適用於多種場景：如地坪塗料、牆面裝飾、樓梯扶手、橋樑修補等。

此類產品在建築行業中，特別是在室內裝修及工業地坪方面，具有廣泛的應用。其優點在於施工簡便、效果持久，且能為建築提供長期的保護與美觀。此外，其良好的粘結性能使其成為修補舊有結構的理想選擇。在交通領域，如機場、港口及道路修補，其高強度與耐載重特性尤為突出。總之，Kelin Epoxy 是一種性能卓越、用途廣泛的環氧樹脂材料。



此類產品在建築行業中，特別是在室內裝修及工業地坪方面，具有廣泛的應用。

Gray 1#

Gray 2#

Gray 3#

Gray 4#

Gray 5#

Gray 6#

Gray 7#

Gray 8#

Gray 9#

Cement Gray

Dull Gray

Silver Gray

Metal Gray

Luxury Silver

Glacier White

Calaeatta

Pearl Gold

Slate Gray

Terra Brown

Greyish Green

Yellow Gray

Soft Khaki

Yellowish Brown

Olive Brown

Brownness

Dark Brown

Reddish Brown

Rock Bslack









Clean the tiles and keep it dry



Polish with tile wax except the glazed tile



Open & Watch, both sides can extruded meanwhile



Screw on the nozzle, put on the grout gun



Inclined cut the top of the nozzle in 45°



Squeeze out 60-80cm long grout in the forepart



Evenly squeeze out the tile agent along the gap



Press the grout with professional glue-press tools



Don't touch in 4-5 hours and remove excess grout then.



Keep the tiles dry in 24 hours

□□□□□□□□□□□□□□□□□□□□□□□□



Two Component Caulking Gun



02




03



04



05



06



07



08



09

Cutter Knife

Pointing trowel

Brush

Forming Stick

Perching Knife

Masking Tape

Stainless Steel Ball

Cleaning Awl

□□□□□□



□□□□□□□□□□



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

□□□□□□□□

